

STREET ENHANCED 4x4 CLASSES

1. Weight classes to be: 5500lbs 6000lbs
2. Headers allowed and may be open and must exit straight back through hood
3. Solid suspension allowed
4. Engine must be in its original location intended by manufacturer
5. Hitch height not to exceed 26 inches – no part of hitch may extend past center line of rear end – No floating hitches – Hitch point can be no less than 36% of wheel base (example 131" wheelbase – hitch can be no less than 47 1/8" from center of axle) Must come to the start line with a minimum of 3" opening and be easily accessible.
6. D.O.T. approved tires – tread width not to exceed 12 1/2 inches.
7. Single carburetor only.
8. Must be pump gas or diesel only
9. No nitrous oxide or methanol – a one year and 10 day disqualification if caught using.
10. Stock front bumpers must be in factory location
11. Front weight may not exceed more than 60" from centerline of axle
12. No dual wheel – crew cabs – 10 cylinders
13. Aluminum heads allowed to be able to run in other area pulls.

SAFETY

1. Drive shaft must have at least 2 loops on each shaft a minimum of 3/4" wide and 1/8" thick steel with a minimum clearance of 2"
 - a. Vehicles that have a shaft between the transmission and transfer case need only 1 loop if the shaft is not more than 12" long and loop is in the middle.
 - b. All driveline U-Joints are to be enclosed in a 360 degree shield 1/4" thick steel or 3/8" metal. All U-Joint covers must be a minimum of 6" wide and a maximum of 2" clearance from U-Joint. Shield should restrain any broken parts. Joint should not be visible from side, top or bottom.
2. All drive axles must be covered with a shield with a hole in center to lock and unlock hubs.
 - a. Must be hooked behind the wheel or on the wheel with bolts and nuts
 - b. All shields must be metal – no snap on wheel covers allowed
3. All torque converters and automotive transmissions must have a shielding of a 4.1 rating or better – extend from rear of engine block to front of tailhousing.
 - a. Blanket must be fastened forward securely with two snaps on each side, one above crankshaft centerline and one below.
 - b. Blanket must have a minimum of 6 straps. Straps must be 2" wide and not more than 1" spacing between each snap. Blanket should have 6" overlap and be 17" wide.
4. All pulling vehicles using a clutch must have a steel billet flywheel and steel bell housing or blanket to cover. Positively no grey cast metal allowed.
5. Minimum of 2 lb fire extinguisher must be loaded and in vehicle
6. Kill Switches Mandatory.

VIOLETION OF ANY RULE WILL BE A DISQUALIFICATION FOR THE EVENT IN WHICH THE VIOLATION TAKES PLACE – NO POINTS – NO MONEY